

Street Tree and Landscaping Placements



Tree must be 15' or more from alley

Tree must be 25' or more from street light

Plantings recommended to be 5' or more from signs

Plantings recommended to be 10' or more from access ramps and required to be 20' or more from street intersections








Plantings recommended to be 5' or more from hydrants

Tree must be 50' or more from street intersection and stop signs and 10' or more from driveways and hydrants

Plantings recommended to be 5' or more from driveways

Tree must be 10' or more away from utility poles and water shut-off valves

LEGEND

-  Tree
-  Street light
-  Plantings (Max height - 18")
-  Water shut-off
-  Hydrant
-  Access ramps
-  Utility pole

Rev. 5/19/15



Know what's below.
Call before you dig.

TREES:

Trees must be planted at least fifty feet (50') feet from the edge of street intersections, traffic control lights and stop signs, and at least ten feet (10') from driveways and fifteen feet (15') from alleys. No tree may be planted closer than twenty-five feet (25') from a street light and ten feet (10') from a utility pole, water shut-off, hydrant, or gas line lateral.

PLANTINGS:

Plantings may not exceed eighteen inches (18") in height; may not overhang onto the public sidewalk, curb, or roadway; may not be within twenty feet (20') from intersections. Where no public sidewalk exists, a four foot (4') unobstructed path will be identified by Engineering. This area must be kept free from any plantings and also be maintained by the abutting owner.